

CE

SCAN FOR MORE DETAILS



TEXORA™ TX/L COMPACT SLING

Compact Slings are excellent anchor slings and safety lanyards for rescue and rope access. Strong, durable, and easy to use, they are rated for a four-person load with a 100 kN MBS (end to end configuration). The High Tenacity Polyester (HTP) fiber core makes the Compact Sling highly durable and robust. An elastic polyester sleeve surrounds the internal load bearing elements for added protection, compact sizing, and easy handling.

TEXORA™ TX/L WIRE SLING

Strong, durable, and easy to use, the TX/L Wire Sling is designed for building versatile anchors in rescue and rope access. Rated for a two-person load, the TX/L Wire Sling has an internal core of galvanized steel wire that is looped 12 times to generate a 50 kN MBS (end to end configuration) and make the load bearing elements resistant to heat, abrasion, cuts, and impacts. A polyester sleeve surrounds the wire loops to protect them from damage, make them easy to handle, and prevent them from damaging finished surfaces.

TEXORA™ BLACK MAMBA SLING

Built for extreme work environments, Texora's Black Mamba represents a breakthrough in technical safety and versatility. Its para-aramid fiber core has a 450°C (842°F) melting point, and high durability. The PES elastane sheath protects and contains the inner fibers in a lightweight, low-profile, and easy to handle package. Classified to EN standards for two person loads and rated to 49 kN (11,016 LBF) MBS, the Mamba is burly for anchor building and compact enough to carry on the harness or in a pocket. It's the ideal tool for rescue and access in harsh conditions.

| Item # | Model | Length | Weight | Color | Certifications |
|--------|---------------------------|-----------------|-----------------|-------------|--|
| 200400 | Texora TX/L Compact Sling | 1 M (3.28 FT) | 425 G (0.9 LB) | Multi-color | EN 795:2012 TYPE B; EN 354:2010; CEN TS 16415:2013 (4 PEOPLE); ANSI Z359.18:2017 |
| 200401 | Texora TX/L Compact Sling | 2 M (6.56 FT) | 800 G (1.7 LB) | Multi-color | EN 795:2012 TYPE B; EN 354:2010; CEN TS 16415:2013 (4 PEOPLE); ANSI Z359.18:2017 |
| 200402 | Texora TX/L Wire Sling | 1 Meter Sling | 540 G (1.2 LB) | Multi-color | EN 795:2012 TYPE B; CEN TS 16415:2013 (2 PEOPLE) |
| 200403 | Texora TX/L Wire Sling | 2 Meter Sling | 1020 G (2.2 LB) | Multi-color | EN 795:2012 TYPE B; CEN TS 16415:2013 (2 PEOPLE) |
| 200404 | Texora Black Mamba Sling | 0.5 M (1.64 FT) | 60 G (2.1 OZ) | Black | EN 795:2012, TYPE B; EN 354:2010; CEN TS 16415:2013 (2 PEOPLE) |
| 200405 | Texora Black Mamba Sling | 1 M (3.28 FT) | 120 G (4.2 OZ) | Black | EN 795:2012, TYPE B; EN 354:2010; CEN TS 16415:2013 (2 PEOPLE) |
| 200406 | Texora Black Mamba Sling | 1.5 M (4.92 FT) | 180 G (6.3 OZ) | Black | EN 795:2012, TYPE B; EN 354:2010; CEN TS 16415:2013 (2 PEOPLE) |
| 200407 | Texora Black Mamba Sling | 2 M (6.56 FT) | 240 G (8.5 OZ) | Black | EN 795:2012, TYPE B; EN 354:2010; CEN TS 16415:2013 (2 PEOPLE) |