









CLASSIFIED TO NFPA 2500 TECHNICAL USE



SWIVO combines a swivel, pulley, and oval carabiner into a single device for building compact rope systems. With its rounded carabiner frame, SWIVO clips easily into the CAPTO becket and other wide attachment points, improving load distribution, simplifying transitions, and maximizing travel in the haul system.

SWIVO excels in M/A systems and works well in combination with high anchors, tripods, and redirects. Teaming up with Rock Exotica, CMC is offering SWIVO in single and double sheave models. SWIVO is patented, made in the USA, and brought to you by two companies committed to quality and service.

## **FEATURES**

- · Combines a swivel, pulley, and oval carabiner in a single device
- · Compact size reduces system length, allowing more travel
- · Connects easily to wide attachment points like the CAPTO becket
- · Oval frame improves load distribution and reduces binding
- Simplifies M/A systems including a 5:1 with CAPTO and CLUTCH
- · Ergonomic design for clipping and loading with one hand
- · Pivoting sideplate allows rope loading without disconnecting
- · Double-action detent button prevents accidental opening
- 1.1" sheave is compact and lightweight for a range of applications
- Sheave is mounted on sealed ball bearings for high efficiency
- · Rotating swivel aligns rope with the direction of pull
- Prusik minding sideplate prevents entanglement
- Double sheave pulley is equipped with integrated becket
- Compatible with rope up to 13 mm (1/2 in)
- Ideal for rescue, work at height, and tree care







Item #	Model	Weight	Pulley Type	Sheave Material	Height x Width	Color	NFPA	CE	3 Sigma MBS
300350	Pulley, SWIVO, 1.1", PMP, Single	209 g (.46 lb)	Single Sheave	Aluminum	163 x 64 mm (6.4 x 2.5 in)	Black	T-rated	EN 12278 EN 12275/B EN 362/B	23 kN (5,170 lbf)
300352	Pulley, SWIVO, 1.1", PMP, Double	308 g (.68 lb)	Double Sheave	Aluminum	185 x 66 mm (7.3 x 2.6 in)	Black	T-rated	N/A	23 kN (5,170 lbf)