

**IMPORTANT INFORMATION - PLEASE READ AND SAVE**



**Pick Off  
Strap**

**Made in USA**  
of US and foreign components

**REPAIR**

All repair work shall be performed by the manufacturer. All other work or modifications void the warranty and releases CMC from all liability and responsibility as the manufacturer.

**SAMPLE INSPECTION AND MAINTENANCE LOG**

The sample log suggests records that should be maintained by the purchaser or user of life safety equipment.

Equipment Inspection and Maintenance Log			
Item _____ # _____	Date in Service _____		
Brand/Model _____	Strength _____		
Date	How Used or Maintained	Comments	Name

**! WARNING**

- **SERIOUS INJURY OR DEATH MAY RESULT FROM THE IMPROPER USE OF THIS EQUIPMENT.**
- **THIS EQUIPMENT HAS BEEN DESIGNED AND MANUFACTURED FOR USE BY EXPERIENCED PROFESSIONALS ONLY.**
- **DO NOT ATTEMPT TO USE THIS EQUIPMENT WITHOUT PRIOR TRAINING.**
- **THOROUGHLY READ AND UNDERSTAND ALL LABELS AND INSTRUCTIONS BEFORE USE.**
- **USE, INSPECT AND REPAIR ONLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.**

**CMC Rescue, Inc.**

6740 Cortona Drive, Goleta CA 93117  
USA  
805-562-9120 / 800-235-5741  
cmcpro.com

**ISO 9001 Certified**

©2018 CMC Control No. 201106.01.012418

**USER INFORMATION**

User Information shall be provided to the user of the product. CMC recommends separating the User Information from the equipment and retaining the information in a permanent record. CMC also recommends making a copy of the information to keep with the equipment and that the information should be referred to before and after each use.

**INSPECTION**

Inspect the equipment according to your department's policy for inspecting life safety equipment. Inspect the equipment prior to entry into service, after each use, and at least once every 12 months. The equipment should be thoroughly inspected by an inspector that meets your department's training standard for inspection of life safety equipment. Keep a record of the date, person performing the inspection and results, as well as the date of first use, name of users and any other pertinent information necessary to keep accurate track of the equipment's usage history in the equipment log or on a tag that attaches to the equipment. Each user should be trained in equipment inspection and should inspect the equipment before each use.

When inspecting the equipment, check the webbing and rope for cuts, worn or frayed areas, broken fibers, soft or hard spots, discoloration, or melted fibers. Check the stitching for pulled threads, abrasion, or breaks. Check the hardware for damage, sharp edges, and improper operation. If any of the above is noted, or if the equipment has been subjected to shock loads, fall loads, or abuse other than normal use, remove the equipment from service and destroy it. If there is any doubt about the serviceability of the equipment, remove the equipment from service and destroy it.

The service life of equipment depends greatly on the type of use and the environment of use. Because these factors vary greatly, a precise service life of the equipment cannot be provided.

**USE**

1.) Using a locking carabiner, connect the V-ring Adjuster into your lowering system. Secure the D-ring in a location that will not be in the way of the descent, such as on your harness gear loop.

2.) When you reach the subject, connect the D-ring into his harness with a locking carabiner. Position yourself and adjust the length of the strap (using the V-ring Adjuster) so the subject is where you want him to be, and the Pick Off Strap is under tension. This reduces the risk of shock loading the system when you add the subject's weight.

Although we have found that the strap works best in this configuration, the D-ring may be attached to the lowering system and the V-ring attached to the subject's harness.

When used in conjunction with the CMC Lifesaver Victim Harness (Part No. 202405):

1.) Connect the D-ring to the Victim Harness tie-in point with a locking carabiner prior to your descent.

2.) Secure the Victim Harness to the subject and remove the slack by adjusting the length of the Pick Off Strap.

For easy carry and handling, the Pick Off Strap and Lifesaver Victim Harness may be kept in the storage bag. The CMC Pick Off Strap works best in a lowering based pick off, but may also be used in rappel pick off. Contact the CMC Rescue School at (800) 235-5741 for more information.

**CARRYING, MAINTENANCE & STORAGE**

During use, carrying and storage keep the equipment away from acids, alkalis, exhaust emissions, rust and strong chemicals. Do not expose the equipment to flame or high temperatures. Carry the equipment where it will be protected as the equipment could melt or burn and fail if exposed to flame or high temperatures.

If the equipment becomes soiled, it can be washed in cold water with a mild detergent that is safe for use with nylon and polyester. Dry out of direct sunlight. Do not dry in an automatic dryer. Store in a cool, dry location. Do not store where the equipment may be exposed to moist air, particularly where dissimilar metals are stored together.